

# KLIPSCH PIC-800-SW-T

8" IN-CEILING SUBWOOFER

# Klipsch®



### MORE BASS, LESS SPACE WITH THE ALL-NEW TRACTRIX® HYPERFOLD PORT™

Klipsch is all about high efficiency, low distortion. Building upon that legacy, we're introducing the all-new patented Tractrix® Hyperfold Port™ engineered to extend port length for maximum bass power via proprietary five-step folded design. Its increased airflow eliminates chuffing and port noise while providing a greater dispersion pattern for larger coverage areas.

### EXCLUSIVE PATENTED SKY HOOK® PRO SYSTEM FOR FASTER, TOOL-FREE INSTALLATION

The Klipsch PIC-800-SW-T was engineered for once the hole is cut. After that, this tool-free installation is a breeze with the exclusive patented Sky Hook® Pro. Utilizing this new technology means you no longer need to worry if the screw gun is set to the correct torque (if you're even using one). A simple click of four buttons and the PIC-800-SW-T is installed.

### IPX6 RATED FOR CHALLENGING COMMERCIAL ENVIRONMENTS

Perfect for commercial projects around the globe, the Klipsch PIC-800-SW-T is IPX6 Rated. Your clients will rest easy knowing their new speakers will have maximum weather resistance for even the most challenging environments.

### BLACK AND WHITE PAINTABLE GRILLE OPTIONS INCLUDED

Meant to fit into any space, the Klipsch PIC-800-SW-T comes with both a black and white grille in the box.

### PHOENIX CONNECTOR FOR SIMPLIFIED INSTALLATION

The PIC-800-SW-T employ a phoenix connector for quick and intuitive connection..

## SPECIFICATIONS

FREQUENCY RESPONSE <sup>1</sup>	40Hz-200kHz +/- 4dB, 32Hz -10dB
POWER HANDLING <sup>2</sup>	150 watts (25.4V) 40Hz-200Hz (600 watts peak)
CALC. MAX. CONT. OUTPUT <sup>3</sup>	108dB
SENSITIVITY <sup>4</sup>	89dB
COVERAGE	N/A
DIRECTIVITY INDEX	N/A
NOMINAL IMPEDANCE	8 ohms 4.2 ohms at 40Hz minimum
TRANSDUCERS	8" woofer 1" titanium compression driver, on a K-1200M Tractrix horn/tweeter bridge
ENCLOSURE MATERIAL	All Weather Abs Plastic, Paintable; Metal Can
ENCLOSURE TUNING	Vented via 3 folded TRACTRIX ports
INPUT CONNECTORS	4 pin euro block
TRANSDUCERS	70V: 70W, 35W 1100V: 70W, 35W Bypass position: 8ohms nominal
CUTOUT DIMENSION	12.5"
MOUNTING DEPTH	10.313"
OVERALL DEPTH	10.375"
OVERALL OVERALL WIDTH	13.625"
THRU HOLE WIDTH	12.313"
WEIGHT	27 lbs

### [FOR LIT POLARS CLICK HERE](#)

<sup>1</sup>1m, half space, anechoic

<sup>2</sup>AES standard, continuous pink noise, 6db peaks

<sup>3</sup>Calculated at 1m at power handling power input

<sup>4</sup>SPL at 1m half space, anechoic with 2.83v pink noise input