araknis N E T W O R K S

Features and Specifications

- Built-in mounting tabs with included screws and anchors.
- 802.3af/at compliant; automatically detects and provides the • required voltage and power for compliant devices.
- Gigabit Ethernet ports support full duplex 10/100/1000Mbps
- Power Input: 100-240V AC, 50-60Hz, 0.8A
- PoE Output: 54V 0.6A DC. 30W max
- Operating Temperature: -4 to 104° F (-20 to 40° C)

Installation

Mount injector and connect Ethernet cables, then connect power. PWR LED = solid green when powered on.

- 1. PoE device output
- en on 2. LAN cable input (APDD) 3. AC power inlet āraknis N-ACC-INJ-POE-30W 4. Mounting screws and anchors 5. PWR LED 5 4 ò PoE PWG LAN 10

FCC Warning

This device has been tested and found to comply with limits for a Class A digital device, pursuant to Part 15 of FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates and radiates radio frequency energy and, if not installed and used in accordance with the user's manual, it may cause interference in which case users will be required to correct interference at their own expenses.

CE Warning

This is a Class A product. In a domestic environment, this product may cause radio interference in which case the user may be required to take adequate measures.

Warranty

Araknis Networks[®] products have a 2-Year Limited Warranty. This warranty includes parts and labor repairs on all components found to be defective in material or workmanship under normal conditions of use. This warranty shall not apply to products which have been abused, modified or disassembled. Products to be repaired under this warranty must be returned to SnapAV or a designated service center with prior notification and an assigned return authorization number (RA).

Technical Support

Phone: 866.838.5052

Email: support@araknisnetworks.com