




8K 1x8 Distribution Amplifier AC-DA-18X2

The AVPro Edge AC-DA-18X2 is a one-input to eight-output, 48 Gbps HDMI 2.1b distribution amplifier that flawlessly divides incoming HDMI signals up to 8K/60 fps into eight separate output streams. Though designed as a next-gen 48 Gbps device, this does not preclude using the AC-DA-18X2 for large legacy system applications where installation stumbling blocks may be immediately remedied. Generationally dated but functioning displays intersecting in systems with overlapping HDMI and HDCP versions can handcuff a system into resolution downscaling all displays for compatibility. The AC-DA-18X2 enables mixed-display systems to coexist at their native rates, with plenty of available dynamic headroom.



CONNECTION DIAGRAM



PRODUCT SPECIFICATIONS

VIDEO:	
VIDEO RESOLUTIONS	UP TO 8K 60HZ 4:4:4/8K 30HZ 4:4:4/4K 120HZ
HDR FORMATS/RESOLUTIONS	420, 422, 444 (10 AND 12 DEEP COLOR) HDR10, HDR10+, DOLBY VISION, HLG
COLOR SPACE	YUV (COMPONENT), RGB (CSC: REC. 601, REC. 709, BT2020, DCI, P3 D6500)
CHROMA SUBSAMPLING	4:4:4, 4:2:2, 4:2:0 SUPPORTED
DEEP COLOR	UP TO 16 BIT
SCALING (RESOLUTION, OUTPUT 2 & 4 ONLY)	8K TO 4K OR 8K/4K TO 1080P
AUDIO:	
AUDIO FORMATS SUPPORTED HDMI	PCM 2.0 CH, LPCM 5.1 & 7.1, DOLBY DIGITAL, DTS 5.1, DOLBY DIGITAL PLUS, DOLBY TRUEHD, DTS-HD MASTER AUDIO, DTS-X, DOLBY ATMOS
AUDIO FORMATS SUPPORTED EXTRACTED (TOSLINK)	LPCM UP TO 5.1 96KHZ 24 BIT, DOLBY DIGITAL 5.1, DTS HIRES AUDIO
AUDIO FORMATS SUPPORTED EXTRACTED (2CH PORT)	PCM 2 CH
DISTANCE:	
HDMI IN/OUT (4K60 4:4:4)	UP TO 50 FEET (USING BULLET TRAIN HDMI)
HDMI IN/OUT (W/ AOC CABLE) (4K60 4:4:4)	UP TO 130 FEET (USING BULLET TRAIN AOC)
OTHER:	
BANDWIDTH	48 GBPS (FRL 6)
HDCP	HDCP 2.3 AND EARLIER
PORTS:	
HDMI	TYPE A
AUDIO (EXTRACTED DIGITAL)	TOSLINK
AUDIO (EXTRACTED ANALOG)	5 PIN TERMINAL BLOCK (BALANCED)
FIRMWARE	USB C
ENVIRONMENTAL:	
OPERATING TEMPERATURE	23 TO 125°F (-5 TO 51°C)
STORAGE TEMPERATURE	-4 TO 140°F (-20 TO 60°C)
HUMIDITY RANGE	5-90% RH (NO CONDENSATION)
POWER:	
POWER CONSUMPTION (TOTAL)	3 WATTS MAX
POWER SUPPLY	INPUT: AC 100-240V ~ 50/60HZ OUTPUT: DC 12V 3A
DIMENSIONS:	
DIMENSIONS (UNIT ONLY LENGTH/WIDTH/ HEIGHT)	MM: 260.35 X 136.65 X 26.92 INCH: 10.25 X 5.38 X 1.06
DIMENSIONS (PACKAGED LENGTH/WIDTH/ HEIGHT) (KIT)	MM: 314.452 X 182.63 X 94.49 INCH: 12.38 X 7.19 X 3.72
WEIGHT (UNIT)	1.86 LBS (0.84 KG)
WEIGHT (PACKAGED)	2.92 LBS (1.32 KG)

*SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE. MASS & DIMENSIONS ARE APPROXIMATE

KEY FEATURES

48 Gbps Support (8K FLR 6)

Full 8K bandwidth extension (select 10K FRL 3, FRL 4, and FRL 5 resolutions supported). Available dynamic range headroom for any 8K source.

Downscaling

Each HDMI output may be configured for downscaling. An 8K signal may be downscaled to 4K or 1080p, while 4K content may be downscaled to 1080p for systems with legacy display technology.

Extracted Audio

Multi-channel digital audio up to 7.1 may be intercepted from the HDMI stream and output via TOSLINK. 2-channel Analog audio may be output via the 5-pin balanced terminal block; however, note that the source must originate as 2-channel PCM.

Fixed FRL Rate

The FRL rate may be set to a fixed rate from a front panel menu setting or via the device API. First-generation new technology displays may not be able to contend with higher bandwidth signals as the latest models do. Limiting the signal bandwidth to first-gen models in mixed systems maintains system stability.

Extended EDID Management

The AC-DA-14X2 features 20 pre-configured EDID slots, including support for FRL Lanes 3 through 6 and three User EDID slots.

HF-EEODB (HDMI Forum EDID Extension Override Data Block) is also supported. HF-EEODB is used to optionally expose an extension count different than the base block claims, revealing more EDID data. Our deep-look, 4-Block EDID Support analyzes up to 512 bytes of EDID data to ensure HDMI handshake and HDCP compatibility with the latest next-gen displays containing a massive amount of EDID data.

Gaming-Focused HDMI 2.1b Features

Quick Media Switching for multimedia use is based on Variable Refresh Rate technology, developed to ensure smooth gameplay from PS5, Xbox Series X, and PC games. VRR reduces or eliminates artifacts such as image tearing (like tearing a piece of paper), and judder (slow "camera" pans that should be smooth but instead abruptly stutter).

USB Command List Control

The front panel USB-C port enables Windows Input and Output command setup control, assisted by MyUart (available for free download).