

## Accessories and Lenses

<b>Supplied Accessories</b>	Power cable, RGB cable, remote control, AA batteries x 2, lens cover, terminal cover x 2, cable tie x 4, security label, user's manual (concise)
<b>Optional Accessories</b>	USBWL5G wireless adapter
<b>Optional Lenses</b>	7 optional lenses are available: FL720, USL701, FL701, SL712, ML713, LL704, UL705 (This model ships without a lens)
<b>Replacement Parts</b>	
<b>Lamp</b>	Lamp free
<b>Remote Control</b>	HL02806
<b>Filter</b>	UX43481

## Projection Throw Chart

Screen Size 16:10		Throw Distance	
Diagonal	Width	Min	Max
30	25	45	75
80	68	117	198
100	85	146	248
150	127	219	371
200	170	291	494
250	212	363	617
300	254	435	740
600	509	869	1478

Throw Ratio: 1.7 - 2.9 : 1 (distance : width)  
Screen size and throw distance are measured in inches with standard lens ML713.

## Projection Lens Chart

Lens	Inches	Meters
<b>FL720</b>	3.9	0.1
<b>USL701</b>	67 - 87	1.7 - 2.2
<b>FL701</b>	69	1.8
<b>SL712</b>	100 - 151	2.5 - 3.8
<b>ML713</b>	146 - 248	3.7 - 6.3
<b>LL704</b>	240 - 407	6.1 - 10.3
<b>UL705</b>	407 - 691	10.3 - 17.6

Projection distances measured in inches and meters with standard lens and optional lenses when projecting onto a 100" diagonal screen.

## Specifications

Display	<b>Projection Technology</b>	3 LCD, 3 chip technology
	<b>Resolution</b>	WUXGA 1920 x 1200
	<b>Brightness</b>	7,000 ANSI lumens
	<b>Colors</b>	10.7 billion colors
	<b>Aspect Ratio</b>	Native 4:3, 16:9, 16:10, 14:9 and zoom compatible
	<b>Contrast Ratio</b>	2,500,000 : 1
	<b>Throw Ratio (distance : width)</b>	Specifications will vary depending on which lens is used with the projector (1.7 - 2.9 : 1 with standard lens ML713)
Operation	<b>Focus Distance</b>	Specifications will vary depending on which lens is used with the projector (45" - 1478" with ML713)
	<b>Display Size</b>	30" - 600" (100" - 350" with FL720, 60" - 600" with USL701)
	<b>Lens</b>	f = 1.6 - 2.0 mm, x 1.7 motorized zoom, focus and lens shift (with ML713) (This model ships without a lens)
	<b>Lens Shift</b>	Motorized (V: -16.7% to +56.5%, H: +/- 10%)
	<b>Expected Light Source Life*</b>	Approx. 20,000 hours (Normal and Whisper mode), 30,000 hours (Long life 1 mode), 50,000 hours (Long life 2 mode)
	<b>Expected Filter Life**</b>	Approx. 30,000 hours
	<b>Speaker Output</b>	N/A
Compatibility	<b>Keystone</b>	H and V +/- 30° (with ML713)
	<b>Computer</b>	VGA, SVGA, XGA, WXGA, SXGA, WXGA+, WSXGA+, UXGA, WUXGA, MAC 16" (fH : 15 - 106 kHz, fV : 50 - 120 Hz)
	<b>Composite Video</b>	NTSC, NTSC4.43, PAL, PAL-M, -N, SECAM
	<b>Component Video</b>	480i, 480p, 576i, 576p, 720p, 1081i, 1080p,
	<b>HDMI &amp; HDBaseT &amp; Display Port</b>	480i, 480p, 576i, 720p, 1080i, 1080p, 4K* Computer signal *4K supported with HDMI1, HDBaseT and Display Port (Display Port supports 4K (24/25/30 Hz))
	<b>Digital Input</b>	HDBaseT x 1, HDMI x 2, Display Port x 1
	<b>Digital Output</b>	HDMI x 1
Connectors	<b>Computer Input 1</b>	15-pin mini D-sub x 1
	<b>Computer Monitor Output</b>	15-pin mini D-sub x 1
	<b>Video Input</b>	
	<b>Composite Video</b>	RCA jack x 1
	<b>Component Video</b>	15-pin mini D-sub (shared with computer input)
	<b>Audio Input</b>	3.5 mm stereo mini jack x 1, RCA jack (L/R) x 1
	<b>Audio Output</b>	3.5 mm stereo mini jack x 1
	<b>Network LAN Wired</b>	RCA jack x 1 (10 base-T / 100 base-TX)
	<b>Network LAN Wireless</b>	USB-A, IEEE802.11 a/b/g/n/ac - optional wireless adapter required
	<b>HDBaseT</b>	RJ-45 port x 1
	<b>USB</b>	Type A x 1 (wireless network)
<b>Control Terminals</b>	9-pin D-sub x 1 (RS-232 control)	
Ratings & Warranty	<b>Power Supply</b>	AC100-120V / AC220-240V, 50/60Hz
	<b>Power Consumption</b>	520W/500W
	<b>Operating Temperature</b>	32°F - 113°F (0°C - 45°C) under 5,250 ft. 32°F - 104°F (0°C - 40°C) 5,250 ft. - 10,000 ft.
	<b>Dimensions (W x D x H)</b>	22.9" x 16.9" x 8.5" (excluding protrusions)
	<b>Weight</b>	Approximately 40.3 lbs.
	<b>Approvals</b>	UL 60950-1 / cUL, FCC part 15 subpart B Class A
	<b>Warranty</b>	5-year/20,000 hours (whichever occurs first) limited parts and labor

\* Actual light source life will vary by individual light source based on environmental conditions, selected operating mode, user settings and usage. Hours of average light source life specified are not guaranteed and do not constitute part of the product or light source warranty. Light source brightness decreases over time.

\*\* Actual filter life will vary by individual filter based on environmental conditions, selected operating mode, user settings and usage. Hours of expected filter life specified are not guaranteed and do not constitute part of the product warranty.



MX0664-Rev.2-05/19  
All specifications subject to change without notice.  
©2019 Maxell Corporation of America. All Rights Reserved.



Maxell Corporation of America

Toll Free: 1.800.377.5887

Web: www.maxellproav.com

